

DVL500-Compact - 6000 m



Tracking du fond de 0.3 à 175 m. Opérationnel jusqu'à 4000 m

The DVL500-Compact combines the compact design of the standard DVL1000 with the superior bottom-track range of the DVL500. It can fly higher in the water column and closer to the seabed than similar equipment, enabling small vehicles to do bigger jobs.

Highlights

- ✓ Bottom-track from 0.3-175 m range
- ✓ Per-ping and per-beam data quality estimates
- ✓ 6000 m operational depth

Applications

- ✓ Small vehicles requiring longer bottom-track range
- ✓ Compact AUVs with high accuracy requirements
- ✓ Easy integration with leading inertial navigation systems (INS)

Technical specifications

→ Bottom velocity

Single ping std @ 1.5 m/s	0.8 cm/s at 1/2 max altitude
Long-term accuracy	±0.1% / ±0.1 cm/s
Minimum altitude	0.1 m
Maximum altitude	175 m
Velocity resolution	0.01 mm/s
Maximum ping rate	8 Hz max

→ Water tracking

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Minimum range	4.0 m

→ Current profiling

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Velocity resolution	0.1 cm/s
Interval	User-specified Nth ping
Maximum range	70 m
Blanking	0.5 m
Cell size	0.5-4.0 m
Max # cells	140

→ Environmental

Operating temperature	-4 to +40 °C
Storage temperature	-20 to +60 °C
Vibration	IEC60068-2-64
EMC approval	IEC/EN 61000-6-2, 61000-6-3

→ Mechanical

Depth rating	6000 m *
Weight	4.15 kg / OEM 2.5 kg
Weight in water	1.7 kg
Height	185 mm
Diameter	∅ 114 mm

* Les produits DVL1000 livrés avant mars 2024 sont classés en profondeur jusqu'à 4000m et non 6000m. Veuillez contacter Nortek si vous avez des doutes concernant le classement en profondeur de votre instrument.

→ Hardware

Frequency of operation	500 kHz
Beam width	5.8°
Configuration	4-beam Janus array convex transducer, 25° beam angle
Internal memory	16 GB / 64 GB optional

→ Hardware

Frequency of operation	500 kHz
Bandwidth	25% centered at transmit frequency

→ Interfaces

Serial (either serial or Ethernet)	Configurable RS-232 or RS-422, SubConn connector, 8-pin male
Ethernet	10/100 Mbits Auto MDI-X. TCP/IP, UDP/IP, HTTP protocols. Fixed IP / DHCP client /Auto IP address assignment. UPnP and Nortek proprietary instrument discovery over Ethernet. IEEE1588/PTP and NTP for absolute time stamping. Multiple simultaneous data format transmission possible.
Data formats	Nortek proprietary w/ 1 ms time stamp accuracy, NMEA0183, variants of PDx
Trigger	Internal 1, 2, 3, 4, 5, 6, 7 or 8 Hz or Trigger In. Trigger option through command (Ethernet or serial) External TTL or 485 lines: (configurable Rising/Falling/Edges)

→ Sensors

Pressure	0.1% FS /precision better than 0.002% of full scale per sample
Temperature	-4° to +40 °C ± 0.1 °C

→ Power

DC input	12-48 V
Maximum continuous current	1.5 A
Average power	3.0 W*

- Power based on 1 Hz sampling and altitude with greatest transmit pulse.

→ Materials

Standard models	POM and titanium housing
-----------------	--------------------------