

# Signature500



## **Courants moyens et turbulence avec houle directionnelle et ice tracking**

---

The Signature500 ADCP is designed for flexibility. It measures current profiles at up to 8 Hz sampling frequency. It can also measure direct vertical velocity profiles, wave height and direction, and acoustic ranging to ice. The center beam also functions as a biological echosounder, enabling high-resolution measurements of biomass in the water column. All these features can be combined using Nortek's patented concurrent mode technology.

## Highlights

- ✓ Five beams for mean currents and turbulence
- ✓ Wave height and direction
- ✓ Acoustic ranging to ice

## Applications

- ✓ Turbulence studies
- ✓ Tidal turbine operations
- ✓ Studies of tidal currents
- ✓ Sediment transport studies
- ✓ Ice drift and draft studies
- ✓ Vessel-mounted coastal surveying
- ✓ Plankton migration studies
- ✓ Biomass measurements
- ✓ Directional wave measurements
- ✓ Suitable for wave buoys

## Technical specifications

### → Water velocity measurements

Maximum profiling range <sup>1)</sup>	60 m (burst mode), 70 m (average mode)
Cell size	0.5-4 m (5m upon request)
Minimum blanking	0.5 m
Maximum number of cells	256 (burst)/200 (average)
Velocity range (along beam)	User-selectable 2.5 or 5.0 m/s
Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Velocity precision	Broadband processing, consult instrument software
Velocity resolution	0.1 cm/s
Max sampling rate	8 Hz (4 Hz using 5 beams)
Velocity range (horizontal)	±10 m/s (typical) ±20 m/s (upon request)

### → HR option (on 5th beam only)

Velocity range	N/A
Cell size	N/A
Profiling range	N/A
Range velocity limitations	N/A

### → AD2CP measurement modes

Single	Burst or average
Concurrent	Burst and average
Alternate	Single and/or concurrent

### → Echo intensity (along slanted beams)

Sampling	Same as velocity
Resolution/ dynamic range	0.5 dB / 70 dB
Transducer acoustic frequency	500 kHz
Number of beams	5; 4 slanted at 25°, 1 vertical
Beam width	2.9°

### → Echo sounder option

Resolution	6 mm - 0.5 m
Number of bins	11,000
Transmit pulse length	32 μs - 1 ms
Transmit pulse	Monochromatic or pulse compressed (25% BW)
Resolution / dynamic range	0.01 dB / 70 dB

### → Wave measurement option

AST frequency	500 kHz
AST max distance	75 m
Maximum wave measurement depth	60 m
Height range	-15 to +15 m

### → Wave measurement option

Accuracy/resolution (Hs)	< 1% of measured value / 2 cm
Accuracy/resolution (Dir)	2° / 0.1°
Period range	1-50 s
Cut-off period (Hs)	5 m depth; 0.6 sec, 20 m depth; 1.1 sec, 60 m depth; 1.9 sec
Cut-off period (dir)	5 m depth; 1.5 sec, 20 m depth; 3.1 sec, 60 m depth; 5.5 sec
Sampling rate (velocity and AST)	4 Hz

### → Ice measurement option

Parameters	Acoustic ranging to ice, speed and direction, echo sounder data
------------	---

### → Sensors

Temperature:	Thermistor in head (sampled at meas. rate)
Temp. range	-4 to +40 °C
Temp. accuracy/resolution	0.1 °C/0.01 °C
Temp. time response	2 min
Compass:	Solid State magnetometer (max 1 Hz samplerate)
Accuracy/resolution	2° for tilt < 30°/0.01°
Tilt:	Solid State accelerometer (max 1 Hz sample rate)
Accuracy/resolution	0.2° for tilt < 30°/0.01°
Maximum tilt	Full 3D
Up or Down	Automatic detect
Pressure:	Piezoresistive (sampled at meas. rate)
Standard range	0-100 m (inquire for options)
Accuracy/precision	0.1% FS / Better than 0.002% of full scale

### → AHRS option

Accelerometer dynamic range	± 2 g
Gyro dynamic range	± 250°/sec
Magnetometer dynamic range	± 1.3 Gauss
Pitch and roll range /resolution	± 90° (pitch) ± 180° (roll) /0.01°
Pitch and roll accuracy	± 2° (dynamic), ± 0.5° (static, ±30°)
Heading range / resolution	360°, all axis /0.01°
Heading accuracy	± 3° (dynamic), ± 2° (static, tilt < 20°)
Sampling rate	Same as measurement rate (up to 8 Hz)

### → Data recording

Capacity	16 GB, 64 GB or 128 GB (inquire for larger capacity)
Data record	Consult instrument software
Mode	Stop when full

### → Real-time clock

Accuracy	± 1 min/year
----------	--------------

## → Real-time clock

Clock retention in absence of external power	1 year. Rechargeable backup battery.
--	--------------------------------------

## → Data communications

Ethernet	10/100 Mbits Auto MDI-X, TCP/IP, UDP/IP, HTTP protocols, Fixed IP / DHCP client /Auto IP address assignment, UPnP and Nortek proprietary instrument discovery over Ethernet
Serial	Configurable RS-232/RS-422 300-1250000 bps
Recorder download baud rate	20 Mbit/s (Ethernet only) - 1 GB in 6 minutes
Controller interface	ASCII command interface over Telnet and serial

## → Connectors

Depending on configuration	MCBH6F (Ethernet), MCBH8F (serial), MCBH2F-G2 (pwr), optional Souriau M-series metal connector for online use (10M)
----------------------------	---

## → Software

Functions	Deployment planning, instrument configuration, data retrieval and conversion (for Windows®)
-----------	---

## → Power

DC input	12-48 V DC
Maximum peak current	1.5 A
Max. average consumption at 1 Hz	8 W at 1 Hz, Ethernet adds 0.75 W
Typical average consumption	25 mW
Sleep consumption	100 µA, power depending on supply voltage
Transmit power per beam	0.3-30 W, adjustable levels
Ping sequence	Parallel

## → Batteries

Internal	180 Wh alkaline, 540 or 1800 Wh with long canister
Duration	Depending on configuration, consult software

## → Environmental

Operating temperature	-4 to +40 °C
Storage temperature	-20 to +60 °C
Vibration	IEC60068-2-64
EMC approval	IEC/EN 61000-6-2, 61000-6-3
Depth rating	300 m (for 6000 m version, contact Nortek for specifications)

## → Materials

Standard model	POM with titanium fasteners
----------------	-----------------------------

## → Dimensions

Maximum diameter	228 mm
Maximum length with room for internal batteries	274 mm (180 Wh), 464 mm (540 Wh or 1800 Wh Li)

## → Dimensions

Maximum length without room for internal batteries	184 mm
--	--------

## → Weight

In air, no battery	6.4 kg (5.2 kg short)
In water, no battery	-0.35 kg (0.6 kg short)
Battery	1.8 kg